

Kanal 5 Synstolkning - Change of transponder

Kanal 5 Synstolkning will move to a new transponder 23rd of June 2026.

There will be a dual illumination that ends 31st of December 2027.

Old transponder settings:

Satellite: THOR6
Transponder: A05
Downlink frequency: 10778 MHz
Downlink polarisation: Vertical
Symbol rate: 25,0 Msym/sec
FEC: 3/4
DVB-S2, 8PSK, Pilot OFF
Transport Stream ID: 67

New transponder settings:

Satellite: THOR7
Transponder: BSS36
Downlink frequency: 12399 MHz
Downlink polarisation: Horizontal
Symbol rate: 30,0 Msym/sec
FEC: 3/4
DVB-S2, 8PSK, Pilot OFF
Transport Stream ID: 67

Service parameters (no change):

Service name: Kanal 5 Synstolkning
Service ID: 18004
Service Type: 0x19 (25 - HDTV MPEG4)
PMT PID: 904
Video PID: 1318
Audio PID: 4257 (vis dan, MPEG1)
ECM PID: 7103 Conax 0x0B00 (Allente)
ECM PID: 2345 NDS VideoGuard 0x093E (Allente)
ECM PID: 2346 NDS VideoGuard 0x0940 (Allente)
ECM PID: 2344 Nagra 0x188A (Allente)